

DIRECT SOURCE WATER DISPENSERS

STAINLESS STEEL WATER DISPENSERS



FEATURES

- Heavy duty stainless steel cabinet.
- Removable front and side panels that provide extra space for plumbing and electrical installation, servicing, and routine maintenance.
- Flow capacity of hot water 8L/hr and cold water 9L/hr.

MODEL	BF56H	BF60H
POWER	Hot 800W Cold 200W	Hot 750W Cold 200W
DIMENSION (W X H)	43W x 110H cm x 30D	43W x 113H cm x 33D
CAPACITY	5L Hot Tank 3L Cold Tank	5L Hot Tank 3L Cold Tank
TEMPERATURE	Cold water 8-15°C; Hot water 90-100°C	Cold water 8-15°C; Hot water 90-100°C

HOT & COLD WATER DISPENSERS



FEATURES

- High impact and durable plastic cabinet.
- Removable front and side panels that provide extra space for plumbing and electrical installation, servicing, and routine maintenance.
- Flow capacity of hot water 5L/hr and cold water 5L/hr.

MODEL	BF-28H	BF-28T
POWER	Hot 750W Cold 200W	Hot 750W Cold 200W
DIMENSION (W X H)	38W x 104H cm x 40D	40W x 52H cm x 39D
CAPACITY	3L Hot Tank 4L Cold Tank	2L Hot Tank 2L Cold Tank
TEMPERATURE	Cold water 8-15°C; Hot water 85-100°C	Cold water 8-15°C; Hot water 85-100°C

HEAVY DUTY WATER DISPENSERS



FEATURES

- Heavy duty stainless or zinc alloy cabinet for long lasting, easy maintenance and corrosion resistance
- Automatic controls with digital temperature sensor for purified water refilling, heating and chilling.
- Ease of installation and maintenance with removable front and side panels.
- Custom design tank capacity up to 40 litres cold tank or hot tank.

MODEL	BF30H	BF40H
POWER	Hot 1000W Cold 200W	Cold 560W Hot Water 800W
DIMENSION (W X H)	43W x 45D cm x 133H cm	40W x 45D cm x 133H cm
CAPACITY	20L Hot Tank 10L Cold Tank	20L Cold Tank 5L Hot Tank
TEMPERATURE	Cold water 8-15°C; Hot water 90-100°C	Cold water 8-15°C; Hot water 90-100°C

HEAVY DUTY WATER DISPENSERS



FEATURES

- Technologically advanced controller with digital temperature sensor for control of hot water refilling-heating, temperature sensors and system controls.
- Heavy duty stainless or zinc alloy cabinet design for long lasting, easy maintenance and corrosion resistance.
- Ease of installation and maintenance with removable front and side panels.

MODEL	BF-20L	BF-50L	BF-25L8I
POWER	Hot 3600W	Hot 3600W	Hot 3600W Cold 200W
DIMENSION (W X H)	39 x 21 x 70	57 x 27 x 70	57 X 27 X 70
CAPACITY	20L Hot Tank	50L Hot Tank	20L Hot Tank 8L Cold Tank
TEMPERATURE	Hot: 80-100°C	Hot: 80-100°C	Hot: 80-100°C